







**Top Down
Furler Systems**

[PRODUCT](#) [SUPPORT](#) [SEARCH](#)

[Go >](#) [HOME](#)

Current Region: [World](#)

[NEXT RANGE DOWN >](#)
[BACK TO PRODUCT RANGE >](#)
[NEXT RANGE UP >](#)

[RANGE SELECTION ADVICE & DEFINITION >](#)

RF55111

BB Series 55 Ball Bearing

Orbit Block™

Single, becket

[Product Information](#) | [Applications](#) | [Materials](#) | [Related Items](#)

FEATURES

- Ultra Lightweight
- Low friction 2-stage Orbital ball bearing system
- Highest working load in its class
- Low profile and compact
- High performance cleating
- Easily fitted and securely retained Dyneema Link head
- Ultra low profile becket

	IMPERIAL <input checked="" type="radio"/> METRIC
Sheave Ø	55 mm
Max. Rope Ø	10 mm
Max. Cable Ø	- mm
Pin Ø	- mm
M.W.L.	500 kg
B. L.	1000 kg
Weight	75 g



* **Total block load.** Load on becket not to exceed 50% of block load. ie. MWL 250kg (550lb), BL 500kg (1100lb). Suitable for 2:1 system at rated block load.

PRODUCT INFORMATION

Lightweight

Kilogram for kilogram of working load, BB and RT Orbit Blocks™ are the world's lightest. The unique orbital design allows the bearing to only be in the active areas of the floating sheave. This minimises the mass of the inactive return race and hub. Weight and bulk are further reduced in the different block configurations. The ball bearing single and becket block has a through-sheave becket arrangement. The result? The lowest weight possible.

Multi-sheave blocks have only single intermediate cheeks and an ultra-light and efficient head arrangement. This gives a 30% weight saving advantage over the nearest competitor. Other brands just link together their single blocks. This results in unnecessary double cheeks between each sheave, held together by a heavy steel channel across the top of the block.

Highest working load in its class

The orbital ball-bearing arrangement gives the largest possible bearing race diameter. This maximises load performance. The proven Ronstan 2-stage bearing system features high compression grade acetal ball bearings and a secondary full-contact bearing. This gives minimum friction across the full working load range.

The floating sheave and bearing system is supported by a fibre-reinforced load frame. The design was computer modelled to be stress optimised. The Dyneema® Link is produced from FSE Robline SK75 fibre, which is 10 times stronger and lighter than steel, and provides the final connection from the block to the load point.



[BACK TO TOP ^](#)

APPLICATIONS

- Mainsheet systems on dinghies, sportsboats and small keelboats to 9m (30ft)
- Spinnaker sheets on dinghies, sportsboats and small keel boats to 9m (30ft)
- Halyard, Vang and Backstay application on boats to 8m (26ft)
- Control line applications on larger yachts

[BACK TO TOP ^](#)

MATERIALS

- Ball bearings - High compression strength carbon black Acetal
- Stage 2 bearing - Carbon fibre reinforced, PTFE impregnated Nylon
- Frame/Cheeks - Toughened, glass fibre reinforced Nylon

- Rope Link: UV stabilised, multi-strand impregmented SK75 Dyneema®

[BACK TO TOP ^](#)

RELATED ITEMS

	Product No.	Description
	RF2455 >	BB & RT Orbit Block™ Accessories, , Stand-up base, suits S55 BB & RT,
	RF50001 >	BB & RT Orbit Block™ Accessories, , Retainer clip, S55 BB & RT single & fiddle Orbit Blocks™,
	RF9004-08 >	BB & RT Orbit Block™ Accessories, , Dyneema® link, S40 BB double & triple Orbit Blocks™, S55 BB & RT single & fiddle Orbit Blocks™, Ø4mm x ID 80mm,

[BACK TO TOP ^](#)

Ronstan WORLD

- [Home](#)
- [Full Product Overview](#)
- [Product Support & Information](#)
- [Custom Products & Solutions](#)
- [News](#)
- [Downloads](#)
- [Company](#)
- [Find a Stockist](#)

Contact Us:

- Email: office@ronstan.com.au

Also visit:

- [Ronstan Tensile Architecture](#)