RF55501



Series 55 Ball Bearing

Orbit Block™

Fiddle³

Product Information | Applications | Materials | Related Items

FEATURES

- Ultra Lightweight
- Low friction 2-stage Orbital ball bearing system
- Highest working load in its class
- Low profile and compact
- High performance cleating
- Easily fitted and securely retained Dyneema Link head

Sheave Ø 55 + 35 mm Max. Rope Ø 10 mm Max. Cable Ø - mm Pin Ø - mm M.W.L. 500 kg B. L. 1000 kg Weight 95 g



Fiddle sheave has a high load full contact bearing (ie.not ball bearing). Main sheave has two-stage, ball bearing.

PRODUCT

Lightweight

Kilogram for kilogram of working load, BB and RT Orbit Blocks™ are the world's lightest. The unique orbital design allows the bearing to only be in the active areas of the floating sheave. This minimises the mass of the inactive return race and hub. Weight and bulk are further reduced in the different block configurations. The ball bearing single and becket block has a through-sheave becket arrangement. The result? The lowest weight possible.

Multi-sheave blocks have only single intermediate cheeks and an ultra-light and efficient head arrangement. This gives a 30% weight saving advantage over the nearest competitor. Other brands just link together their single blocks. This results in unnecessary double cheeks between each sheave, held together by a heavy steel channel across the top of the block.

The orbital ball-bearing arrangement gives the largest possible bearing race diameter. This maximises load performance. The proven Ronstan 2-stage bearing system features high compression grade acetal ball bearings and a secondary full-contact bearing. This gives minimum friction across the full working load range.

The floating sheave and bearing system is supported by a fibre-reinforced load frame. The design was computer modelled to be stress optimised. The Dyneema® Link is produced from FSE Robline SK75 fibre, which is 10 times stronger and lighter than steel, and provides the final connection from the block to the load point.

Fiddle block flexibility

Becket fiddle blocks use a Dyneema® Link attachment for the sheet termination and are suitable for both spliced and unspliced lines. If you need additional purchase, a becket take-off can be simply added to any fiddle block version just by adding a Dyneema® Link.



APPLICATIONS

- Mainsheet systems on dinghies, sportsboats and small keelboats to 9m (30ft)
- Spinnaker sheets on dinghies, sportsboats and small keel boats to 9m (30ft)
- Halyard, Vang and Backstay application on boats to 8m (26ft)
- Control line applications on larger yachts

MATERIALS

- Ball bearings High compression strength carbon black Acetal
- Stage 2 bearing Carbon fibre reinforced, PTFE impregnated Nylon
- Frame/Cheeks Toughened, glass fibre reinforced Nylon
- Rope Link: UV stabilised, multi-strand impregmented SK75 Dyneema®

Product No.

RF2455 > BB & RT Orbit Block™ Accessories, , Stand-up base, suits S55 BB & RT,

RF50001 > BB & RT Orbit Block™ Accessories, , Retainer clip, S55 BB & RT single & fiddle Orbit Blocks™,

RF9004-08 > BB & RT Orbit Block™ Accessories, , Dyneema® link, S40 BB double & triple Orbit Blocks™, S55 BB & RT single & fiddle Orbit Blocks™, Ø4mm x ID 80mm,

Ronstan WORLD

Home

- Full Product Overview
- Product Support & Information
- Custom Products & Solutions
- News
- Downloads
- Company
- Find a Stockist

Contact Us:

■ Email: office@ronstan.com.au

Also visit:

Ronstan Tensile Architecture