



PRODUCT SUPPORT SEARCH  
[BACK TO PRODUCT RANGE](#) [NEXT RANGE UP](#) >

Go > HOME

Current Region: World



**Top Down  
Furler Systems**

## RF64151

 Series 60

### Foot, single

[Product Information](#) | [Applications](#) | [Materials](#) | [Related Items](#)

#### FEATURES

- Class leading performance and sleek, contemporary styling
- Excellent dynamic and high static load performance
- Less than half the friction of the nearest competitor
- Durable aluminium alloy cheek plates
- Central hub hole can be used as a becket take-off or tie-up point
- Only two fastener holes - minimises deck sealing considerations
- Scalloped cheeks - allows for variations in line lead

● IMPERIAL METRIC

Sheave Ø	2 3/8 in.
Max. Rope Ø	1/2 in.
Max. Cable Ø	- in
Pin Ø	- in.
M.W.L.	2200 lb.
B. L.	4410 lb.
Weight	6.4 oz.

\* Suits 2 x 8mm (5/16") screws (not inc.)



#### PRODUCT INFORMATION

Core Blocks™ are a true all round solution. A tuned 2-stage bearing system provides excellent performance across the full working load range with an integrated thrust bearing feature and the resilience to handle high dynamic or static loads. Acetal sheave, alloy cheeks and stainless fixings complete the durable package. For reliability and a long service life, these blocks are the right choice for sheets, halyards and control line applications for cruising and racing.

##### Universal Bearing -

Dynamic and high static load performance

The Ronstan Universal Bearing incorporates our proven 2-stage bearing system

Stage 1 - Under moderate loads, Acetal ball bearings ensure minimum friction.

Stage 2 - Under heavy loads, where deformation of ball bearings alone would result in increased friction, a sliding Acetal bearing on a polished stainless steel race takes over, maintaining low friction performance.

Additionally the ball bearings are configured to act as a thrust bearing between the sheave and cheeks, preventing the sheave from rubbing on the cheeks and causing friction when the line lead in and out of the block isn't perfect. Particularly important for cheek blocks.

##### Alloy cheek plates

Block cheeks are manufactured from the highest quality alloy for maximum strength. Material optimisation and the cut-away design minimises weight and allows easy fresh water rinsing of salt and debris from the bearings. Cheek design has been further styled with flaring at the block throat and reduced gap between the cheek and sheave, minimising rope wear.



[BACK TO TOP ▲](#)

#### APPLICATIONS

- Ideal for mainsheet, halyard and spinnaker sheet applications on boats to 12m (40ft).
- Various control line applications on larger yachts.
- Alloy sheave models are available for use with wire.

[BACK TO TOP ▲](#)

#### MATERIALS

- Sheave: U.V. stabilised Acetal or anodised aluminium (AW models)
- Cheek plates: Aluminium alloy
- Ball Bearings: High compression strength carbon black Acetal
- Hub: Grade 316 stainless steel.

[BACK TO TOP ▲](#)

Ronstan WORLD

Contact Us:

Also visit:

- [Home](#)
- [Full Product Overview](#)
- [Product Support & Information](#)
- [Custom Products & Solutions](#)
- [News](#)
- [Downloads](#)
- [Company](#)
- [Find a Stockist](#)

- Email: [office@ronstan.com.au](mailto:office@ronstan.com.au)

- [Ronstan Tensile Architecture](#)