



PRODUCT SUPPORT SEARCH
NEXT RANGE DOWN >BACK TO PRODUCT RANGE >

Go > HOME

Current Region: World



**Top Down
Furler Systems**

RF74110

 Series 75


Single, becket

[Product Information](#) | [Applications](#) | [Materials](#) | [Related Items](#)

FEATURES

- Class leading performance and sleek, contemporary styling
- Excellent dynamic and high static load performance
- Less than half the friction of the nearest competitor
- Durable aluminium alloy cheek plates
- Central hub hole can be used as a becket take-off or tie-up point
- Universal head with full 3-axis articulation
- Head posts can be locked at 0 or 90 degrees, by using a 2.5mm Hex/Allen Key
- Removable becket pin for fitting of pre-spliced lines



	 IMPERIAL METRIC
Sheave Ø	3 in.
Max. Rope Ø	9/16 in.
Max. Cable Ø	- in
Pin Ø	5/16 in.
M.W.L.	3300 lb.
B. L.	6600 lb.
Weight	15.1 oz.

PRODUCT INFORMATION

Core Blocks™ are a true all round solution. A tuned 2-stage bearing system provides excellent performance across the full working load range with an integrated thrust bearing feature and the resilience to handle high dynamic or static loads. Acetal sheave, alloy cheeks and stainless fixings complete the durable package. For reliability and a long service life, these blocks are the right choice for sheets, halyards and control line applications for cruising and racing.

Universal Bearing -

Dynamic and high static load performance

The Ronstan Universal Bearing incorporates our proven 2-stage bearing system

Stage 1 - Under moderate loads, Acetal ball bearings ensure minimum friction.

Stage 2 - Under heavy loads, where deformation of ball bearings alone would result in increased friction, a sliding Acetal bearing on a polished stainless steel race takes over, maintaining low friction performance.

Additionally the ball bearings are configured to act as a thrust bearing between the sheave and cheeks, preventing the sheave from rubbing on the cheeks and causing friction when the line lead in and out of the block isn't perfect. Particularly important for cheek blocks.

Alloy cheek plates

Block cheeks are manufactured from the highest quality alloy for maximum strength. Material optimisation and the cut-away design minimises weight and allows easy fresh water rinsing of salt and debris from the bearings. Cheek design has been further styled with flaring at the block throat and reduced gap between the cheek and sheave, minimising rope wear.

Universal head

The head assembly incorporates a brass bearing washer to provide smooth 360° rotation of the post and shackle. A set screw arrangement allows the head to be locked at 0° or 90°.

Shackles are high quality forged grade 316 stainless steel.

Suits pre-spliced lines

Removable becket pins allow fitting of pre-spliced lines. The flush fit becket pin head is kind on deck surfaces and won't snag lines.



[BACK TO TOP](#)

APPLICATIONS

- Ideal for use on mainsheet, spinnaker sheet, vang, halyard and backstay applications on boats up to 14m (46ft).
- General applications on larger yachts.
- Alloy sheave models are available for use with wire.

[BACK TO TOP ^](#)

MATERIALS

- Sheave: U.V. stabilised acetel or anodised aluminium (AW models).
- Cheek plates: Aluminium alloy
- Ball Bearings: High compression strength carbon black acetel.
- Shackle, post & hub: Grade 316 stainless steel.

[BACK TO TOP ^](#)

SPARE PARTS



Product No.	Description
RF618A >	5/16" pin dia., Standard Dee Shackles, Coined pin head,

[BACK TO TOP ^](#)

Ronstan WORLD

- [Home](#)
- [Full Product Overview](#)
- [Product Support & Information](#)
- [Custom Products & Solutions](#)
- [News](#)
- [Downloads](#)
- [Company](#)
- [Find a Stockist](#)

Contact Us:

- Email: office@ronstan.com.au

Also visit:

- [Ronstan Tensile Architecture](#)